


Snowmaking

Avalanche® 2000 II



- Application:** Designed for snowmaking, featuring a high performance construction.
- Tube:** Black, fused thermoplastic which produces an extremely smooth waterway, significantly reducing friction loss compared to conventional liners.
- Reinforcement:** Woven filament polyester
- Cover:** Woven filament polyester
- Temperature:** As low as -55°F (Working)
- Branding:** AVALANCHE® 2000 II
- Lengths:** 50' and 100' standard lengths; (* Any Length Available Upon Request)
- Couplings:** Internally expanded aluminum male NPT threaded couplings or high-performance, quick disconnect couplings.

Part #	Nom ID		Test Pressure		Burst Pressure	
	in	mm	psi	Mpa	psi	Mpa
023-0249-0802	1 1/2	38.1	800	5.52	2000	13.79
023-0329-0802	2	50.8	800	5.52	2000	13.79
023-0409-0802	2 1/2	63.5	800	5.52	1500	10.34



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

JGB® Headquarters
Liverpool, NY 13088
(315) 451-2770

Buffalo Branch
Cheektowaga, NY 14225
(716) 684-8224

Southeast Hub
Charlotte, NC 28273
(704) 588-9920

St. Louis Branch
St. Louis, MO 63111
(314) 256-0833

Williston Branch
Williston, ND 58801
(701) 774-2195

Houston Branch
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com